

LOCKOUT TAGOUT PROGRAM MACHINE SPECIFIC PROCEDURES

NAME OF EQUIPMENT:	
LOCATION OF EQUIPMENT:	
SERIAL NUMBER OF EQUIPMENT:	
DATE OF PROCEDURES:	
DATE OF LAST REVIEW:	

LOCKOUT PROCEDURES

IDENTIFY ENERGY SOURCES & MEANS OF ISOLATION
(i.e. Air, Hydraulic, Steam, Gravity,
Electrical, Stored Energy)

SHUTDOWN: Turn off machine or equipment.

ISOLATION: Isolate machine or equipment from energy source(s) identified

above.

LOCKOUT: Apply Lockout device, tag and lock.

Check to ensure the isolating device is in the SAFE or OFF

position.

RELEASE: Release stored energy.

Relieve, disconnect, restrain, block or otherwise ensure that all

energy sources are de-energized.

VERIFY: Try on-off switch or other controls to be sure the machine

won't start.

Return all switches to **OFF** position.

RESTART

INSPECT: Remove all tools and materials.

Reassemble machine.

Reinstall all guards and safety devices.

NOTIFY: Ensure **ALL EMPLOYEES** are safely positioned.

Ensure all affected employees are notified of the restart.

REMOVE: Remove lockout device(s).

Only the person who applied the device may remove it.